

Printing date 06/17/2015 Reviewed on 06/01/2015

1 Identification

· Product identifier

· Trade name: Chembond® 2000 H.T.A. Thinner

· Article number: HTA Thinner

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier: Chemical Consultants Inc. 1850 Wild Turkey Circle Corona, CA 92880 USA

+1 (951) 735-5511 ncollins@ccidom.com

- · Information department: Product safety department
- · Emergency telephone number: INFOTRAC 1-800-535-5053

2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS07

Eye Irrit. 2A H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms





GHS02

GHS07

- · Signal word Danger
- · Hazard-determining components of labeling:

acetone

ethyl acetate

· Hazard statements

Highly flammable liquid and vapor.

Causes serious eye irritation.

May cause drowsiness or dizziness.

· Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Use explosion-proof electrical/ventilating/lighting/equipment.

Avoid breathing dust/fume/gas/mist/vapors/spray

Wear protective gloves / eye protection / face protection.

Wear eye protection / face protection.

(Contd. on page 2)



Printing date 06/17/2015 Reviewed on 06/01/2015

Trade name: Chembond® 2000 H.T.A. Thinner

(Contd. of page 1)

Ground/bond container and receiving equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Call a poison center/doctor if you feel unwell.

If eye irritation persists: Get medical advice/attention.

In case of fire: Use for extinction: CO2, powder or water spray.

Store locked up.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 1Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = 1Fire = 3

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous o	components:
---------------	-------------

67-64-1	acetone	60-80%
141-78-6	ethyl acetate	20-40%

4 First-aid measures

- · Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.

(Contd. on page 3)



Printing date 06/17/2015 Reviewed on 06/01/2015

Trade name: Chembond® 2000 H.T.A. Thinner

(Contd. of page 2)

· Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- · Environmental precautions: For large spills: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see item 7.

(Contd. on page 4)



Printing date 06/17/2015 Reviewed on 06/01/2015

Trade name: Chembond® 2000 H.T.A. Thinner

(Contd. of page 3)

· Control parameters

· Components with limit values that require monitoring at the workplace:		
67-6	4-1 acetone	
PEL	Long-term value: 2400 mg/m³, 1000 ppm	
REL	Long-term value: 590 mg/m³, 250 ppm	
TLV	Short-term value: (1782) NIC-1187 mg/m³, (750) NIC-500 ppm	
	Long-term value: (1188) NIC-594 mg/m³, (500) NIC-250 ppm	
	BEI	
141-78-6 ethyl acetate		
PEL	Long-term value: 1400 mg/m³, 400 ppm	
REL	Long-term value: 1400 mg/m³, 400 ppm	
TLV	Long-term value: 1440 mg/m³, 400 ppm	
· Ingredients with biological limit values:		
67-6	4-1 acetone	

BEI 50 mg/L

Medium: urine Time: end of shift

Parameter: Acetone (nonspecific)

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- $\cdot \textit{General protective and hygienic measures:} \\$

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 5)



Printing date 06/17/2015 Reviewed on 06/01/2015

Trade name: Chembond® 2000 H.T.A. Thinner

· Eye protection:

(Contd. of page 4)



Tightly sealed goggles

Physical and chemical proper	ties			
· Information on basic physical and chemical properties · General Information				
Appearance:				
Form:	Fluid			
Color:	According to product specification			
Odor:	Characteristic			
Odour threshold:	Not determined.			
pH-value:	Not determined.			
Change in condition				
Melting point/Melting range:	Undetermined.			
Boiling point/Boiling range:	55 °C (131 °F)			
Flash point:	-17 °C (1 °F)			
Flammability (solid, gaseous):	Not applicable.			
Ignition temperature:	460 °C (860 °F)			
Decomposition temperature:	Not determined.			
Auto igniting:	Product is not selfigniting.			
Danger of explosion:	Product is not explosive. However, formation of explosive air/vap mixtures are possible.			
Explosion limits:				
Lower:	2.1 Vol %			
Upper:	13.0 Vol %			
Vapor pressure at 20 $^{\circ}C$ (68 $^{\circ}F$):	233 hPa (175 mm Hg)			
Density at 20 °C (68 °F):	$0.83191 \ g/cm^3 (6.942 \ lbs/gal)$			
Relative density	Not determined.			
Vapour density	Not determined.			
Evaporation rate	Not determined.			
Solubility in / Miscibility with				
Water:	Not miscible or difficult to mix.			
Partition coefficient (n-octanol/wat	er): Not determined.			
Viscosity:	N. J I			
Dynamic:	Not determined.			
Kinematic:	Not determined.			
Solvent content:				
VOC content:	317.0 g/l / 2.65 lb/gl			

(Contd. on page 6)



Printing date 06/17/2015 Reviewed on 06/01/2015

Trade name: Chembond® 2000 H.T.A. Thinner

(Contd. of page 5)

· Other information

No further relevant information available.

10 Stability and reactivity

- · Reactivity
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · LD/LC50 values that are relevant for classification:

67-64-1 acetone

 Oral
 LD50
 5800 mg/kg (rat)

 Dermal
 LD50
 20000 mg/kg (rabbit)

- · Primary irritant effect:
- · on the skin: No irritant effect.
- · on the eye: Irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

- · Carcinogenic categories
- · IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system. (Contd. on page 7)

itu. on page



Printing date 06/17/2015 Reviewed on 06/01/2015

Trade name: Chembond® 2000 H.T.A. Thinner

(Contd. of page 6)

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Dispose of content and/or container in accordance with local, regional, national and/or international regulations.

- · Uncleaned packagings:
- · Recommendation:

Dispose of content and/or container in accordance with local, regional, national and/or international regulations

14 Transport injormatio	ını
· UN-Number	
. DOT IMDG IATA	

· DOT, IMDG, IATA

· UN proper shipping name

· DOT Flammable liquids, n.o.s. (Acetone, Ethyl acetate)

UN1993

· IMDG, IATA FLAMMABLE LIQUID, N.O.S. (ACETONE, ETHYL ACETATE)

· Transport hazard class(es)

 $\cdot DOT$



· Class 3 Flammable liquids

· Label

· IMDG, IATA



· Class 3 Flammable liquids

· Label

· Packing group · DOT, IMDG, IATA

· Environmental hazards:

· Marine pollutant: No

· Special precautions for user Warning: Flammable liquids

II

Danger code (Kemler): 33EMS Number: F-E,S-E

· Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code Not applicable.

(Contd. on page 8)



Printing date 06/17/2015 Reviewed on 06/01/2015

Trade name: Chembond® 2000 H.T.A. Thinner

Contd. of page 7)

Transport/Additional information:

DOT

Quantity limitations
On passenger aircraft/rail: 5 L
On cargo aircraft only: 60 L

IMDG
Limited quantities (LQ)
Excepted quantities (EQ)
Code: E2
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 500 ml

UN''Model Regulation'':
UN1993, Flammable liquids, n.o.s. (Acetone, Ethyl acetate), 3, II

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara
- · Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

- · Proposition 65
- · Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

- · Carcinogenic categories
- · EPA (Environmental Protection Agency)

67-64-1 acetone

I

· TLV (Threshold Limit Value established by ACGIH)

67-64-1 acetone

A4

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

• GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 9)

(Contd. of page 8)



Safety Data Sheet acc. to OSHA HCS

Printing date 06/17/2015 Reviewed on 06/01/2015

Trade name: Chembond® 2000 H.T.A. Thinner

· Hazard pictograms





GHS02

502 GHS0

- · Signal word Danger
- · Hazard-determining components of labeling:

acetone

ethyl acetate

· Hazard statements

Highly flammable liquid and vapor.

Causes serious eye irritation.

May cause drowsiness or dizziness.

· Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Use explosion-proof electrical/ventilating/lighting/equipment.

Avoid breathing dust/fume/gas/mist/vapors/spray

Wear protective gloves / eye protection / face protection.

Wear eye protection / face protection.

Ground/bond container and receiving equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Call a poison center/doctor if you feel unwell.

If eye irritation persists: Get medical advice/attention.

In case of fire: Use for extinction: CO2, powder or water spray.

Store locked up.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact: Mr. Collins
- · Date of preparation / last revision 06/17/2015 / -
- · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

 $DOT: \ US \ Department \ of \ Transportation$

 ${\it IATA: International Air Transport Association}$

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

(Contd. on page 10)



Printing date 06/17/2015 Reviewed on 06/01/2015

Trade name: Chembond® 2000 H.T.A. Thinner

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Flam. Liq. 2: Flammable liquids, Hazard Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

(Contd. of page 9)

TIC