ting date 10/29/2021 Reviewed on 10/29/2021

1 Identification

- · Product identifier
- · Trade name: LTC Nylon Bonding Additive
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Chemical Consultants Inc.

1850 Wild Turkey Circle

Corona, CA 92878

USA

+1 (951) 735-5511

ncollins@ccidom.com

- · Information department: Product safety department
- · Emergency telephone number: INFOTRAC 1-800-535-5053

2 Hazard(s) identification

· Classification of the substance or mixture



GHS08 Health hazard

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Carc. 2 H351 Suspected of causing cancer.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



GHS07

Acute Tox. 4 H332 Harmful if inhaled.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms





GHS07

GHS08

- · Signal word Danger
- · Hazard-determining components of labeling:

4,4'-methylenediphenyl diisocyanate

diphenylmethanediisocyanate, isomeres and homologues

o-(p-isocyanatobenzyl)phenyl isocyanate

· Hazard statements

H332 Harmful if inhaled.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

(Contd. on page 2)



Printing date 10/29/2021 Reviewed on 10/29/2021

Trade name: LTC Nylon Bonding Additive

(Contd. of page 1)

H317 May cause an allergic skin reaction.

H351 Suspected of causing cancer.

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

· Precautionary statements

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P260 Do not breathe dust/fume/gas/mist/vapors/spray.

P264 Wash thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing must not be allowed out of the workplace.
 P280 Wear protective gloves/protective clothing/eye protection/face protection.

P284 [In case of inadequate ventilation] wear respiratory protection.

P302+P352 If on skin: Wash with plenty of water.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P312 Call a poison center/doctor if you feel unwell.

P321 Specific treatment (see on this label).

P314 Get medical advice/attention if you feel unwell.

P362+P364 Take off contaminated clothing and wash it before reuse.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.

P342+P311 If experiencing respiratory symptoms: Call a poison center/doctor.

P363 Wash contaminated clothing before reuse.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

- · Other hazards
- · Results of PBT and vPvB assessment
- \cdot **PBT:** Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:			
101-68-8	4,4'-methylenediphenyl diisocyanate	50-70%	
9016-87-9	diphenylmethanediisocyanate,isomeres and homologues	30-50%	
5873-54-1 o-(p-isocyanatobenzyl)phenyl isocyanate		10-20%	

4 First-aid measures

- · Description of first aid measures
- · General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

(Contd. on page 3)



Printing date 10/29/2021 Reviewed on 10/29/2021

Trade name: LTC Nylon Bonding Additive

(Contd. of page 2)

· After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eve contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- $\cdot \textit{Indication of any immediate medical attention and special treatment needed}$

No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- · Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures Mount respiratory protective device.
- · Environmental precautions: For large spills: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

· PAC-1:		
	4,4'-methylenediphenyl diisocyanate	$0.45 \ mg/m^3$
9016-87-9	diphenylmethanediisocyanate,isomeres and homologues	0.15 mg/m ³
· PAC-2:		
	4,4'-methylenediphenyl diisocyanate	5 mg/m ³
9016-87-9	diphenylmethanediisocyanate,isomeres and homologues	3.6 mg/m^3
· PAC-3:		
101-68-8	4,4'-methylenediphenyl diisocyanate	55 mg/m ³
9016-87-9	diphenylmethanediisocyanate,isomeres and homologues	22 mg/m³

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

(Contd. on page 4)



Printing date 10/29/2021 Reviewed on 10/29/2021

Trade name: LTC Nylon Bonding Additive

(Contd. of page 3)

Open and handle receptacle with care.

Prevent formation of aerosols.

- · Information about protection against explosions and fires: Keep respiratory protective device available.
- · Conditions for safe storage, including any incompatibilities
- Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

101-68-8 4,4'-methylenediphenyl diisocyanate

PEL Ceiling limit value: 0.2 mg/m³, 0.02 ppm

REL Long-term value: 0.05 mg/m³, 0.005 ppm

Ceiling limit value: $0.2* mg/m^3$, 0.02* ppm

*10-min

TLV Long-term value: 0.005 ppm

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

· Breathing equipment:

Not required.

Personal protective equipment should be selected based on an assessment of risk of exposure as uses and conditions of use vary and there is no single PPE scenario that fits all. There are chemicals in the blend that evaporate into the air and under conditions of large use volumes in combination with limited ventilation, respiratory protection may be warranted. Conditions where the worker uses the product in small amounts with local exhaust ventilation, protective gloves and eye protection may be sufficient to control exposure

Personal protective equipment should be selected based on an assessment of risk of exposure as uses and conditions of

use vary and there is no single PPE scenerio that fits all. There are solvents in the blend that evaporate into the air and

under conditions of large use volumes in combination with limited ventilation, respiratory protection may be warranted.

Conditions where the worker uses the product in small amounts with local exhaust ventilation, protective gloves and

eye protection may be sufficient to control exposure

(Contd. on page 5)

(Contd. of page 4)



Safety Data Sheet acc. to OSHA HCS

Printing date 10/29/2021 Reviewed on 10/29/2021

Trade name: LTC Nylon Bonding Additive

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

· Information on basic physical and chemical proper		
· General Information		
· Appearance:		
Form:	Fluid	
Colom	According to prod	

Color: According to product specification

Color:	According to product specification
· Odor:	Characteristic
· Odor threshold:	Not determined.
Out in estitue.	1101 uctof mineu.
· pH-value:	Not determined.
· Change in condition	
Melting point/Melting range:	Undetermined.
	•
Boiling point/Boiling range:	190 °C (374 °F)
· Flash point:	203 °C (397.4 °F)
· Flammability (solid, gaseous):	Not applicable.
1 tummubuny (sonu, guscous).	1101 applicable.
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product does not present an explosion hazard.
· Explosion limits:	
Lower:	Not determined.
	Not determined.
Upper:	Noi determined.
· Vapor pressure at 20 °C (68 °F):	0 hPa
· Density at 20 °C (68 °F):	1.23 g/cm³ (10.26435 lbs/gal)
· Relative density	Not determined.
Remire acusuy	roi acierminea.

(Contd. on page 6)



Printing date 10/29/2021 Reviewed on 10/29/2021

Trade name: LTC Nylon Bonding Additive

		(Contd. of page
Vapor density	Not determined.	
Evaporation rate	Not determined.	
Solubility in / Miscibility with		
Water:	Not miscible or difficult to mix.	
Partition coefficient (n-octanol/we	tter): Not determined.	
Viscosity:		
Dynamic at 20 °C (68 °F):	65-115 mPas	
Kinematic:	Not determined.	
Solvent content:		
VOC content:	0.00 %	
	0.0 g/l / 0.00 lb/gal	
Solids content:	100.0 %	
Other information	No further relevant information available.	

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· LD/LC50 values that are relevant for classification:	
ATE (Acute Toxicity Estimate)	
Inhalative LC50/4 h 1.5 mg/l	

101-68-8 4,4'-methylenediphenyl diisocyanate

Oral | LD50 | 2,200 mg/kg (mouse)

- Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: Irritating effect.
- · Sensitization:

Sensitization possible through inhalation.

Sensitization possible through skin contact.

· Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Harmful

Irritant

(Contd. on page 7)



Printing date 10/29/2021 Reviewed on 10/29/2021

Trade name: LTC Nylon Bonding Additive

(Contd. of page 6)

Carcinogenic categories

· Carcinogenic categories			
· IARC (International Agency for Research on Cancer)			
101-68-8 4,4'-methylenediphenyl diisocyanate	3		
9016-87-9 diphenylmethanediisocyanate,isomeres and homologues	3		
· NTP (National Toxicology Program)			
None of the ingredients is listed.			
· OSHA-Ca (Occupational Safety & Health Administration)			
None of the ingredients is listed.			

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · **Mobility in soil** No further relevant information available.
- · Additional ecological information:
- · General notes:

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Dispose of content and/or container in accordance with local, regional, national and/or international regulations.

- · Uncleaned packagings:
- · Recommendation:

Dispose of content and/or container in accordance with local, regional, national and/or international regulations

· UN-Number	
$\cdot DOT$	UN3082
· IMDG, IATA	not regulated
· UN proper shipping name	
$\cdot DOT$	Environmentally hazardous substance, liquid, n.o.s. (4,4 methylenediphenyl diisocyanate)
· IMDG, IATA	not regulated



Printing date 10/29/2021 Reviewed on 10/29/2021

Trade name: LTC Nylon Bonding Additive

(Contd. of page 7)

· Transport hazard class(es)

 $\cdot DOT$



· Class 9 Miscellaneous dangerous substances and articles

· Label

· ADN/R Class: not regulated

· Packing group

· DOT

· IMDG, IATA not regulated

• Environmental hazards: Not applicable.

· Special precautions for user Not applicable.

· Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code Not applicable.

· UN "Model Regulation": not regulated

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.
- · Sara
- · Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

101-68-8 4,4'-methylenediphenyl diisocyanate

9016-87-9 diphenylmethanediisocyanate, isomeres and homologues

· TSCA (Toxic Substances Control Act):

All components have the value ACTIVE.

· Hazardous Air Pollutants

101-68-8 4,4'-methylenediphenyl diisocyanate

- · Proposition 65
- · Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· New Jersey Special Hazardous Substance List:

None of the ingredients is listed.

(Contd. on page 9)



Printing date 10/29/2021 Reviewed on 10/29/2021

Trade name: LTC Nylon Bonding Additive

(Contd. of page 8)

· Pennsyl	lvania	Righ	ht-to-l	Know	List:

101-68-8 4,4'-methylenediphenyl diisocyanate

· Pennsylvania Special Hazardous Substance List:

101-68-8 4,4'-methylenediphenyl diisocyanate

|E|

· Carcinogenic categories

· EPA (Environmental Protection Agency)				
101-68-8	4,4'-methylenediphenyl diisocyanate	D, CBD		
9016-87-9	diphenylmethanediisocyanate,isomeres and homologues	CBD		

· TLV (Threshold Limit Value)

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms





GHS07

GHS08

· Signal word Danger

· Hazard-determining components of labeling:

4,4'-methylenediphenyl diisocyanate

diphenylmethanediisocyanate,isomeres and homologues

o-(p-isocyanatobenzyl)phenyl isocyanate

· Hazard statements

H332 Harmful if inhaled.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 May cause an allergic skin reaction.

H351 Suspected of causing cancer.

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

· Precautionary statements

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P260 Do not breathe dust/fume/gas/mist/vapors/spray.

P264 Wash thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing must not be allowed out of the workplace.
P280 Wear protective gloves/protective clothing/eye protection/face protection.

P284 [In case of inadequate ventilation] wear respiratory protection.

P302+P352 If on skin: Wash with plenty of water.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P312 Call a poison center/doctor if you feel unwell.

P321 Specific treatment (see on this label).

(Contd. on page 10)



Printing date 10/29/2021 Reviewed on 10/29/2021

Trade name: LTC Nylon Bonding Additive

(Contd. of page 9)

P314 Get medical advice/attention if you feel unwell.

P362+P364 Take off contaminated clothing and wash it before reuse.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.

P342+P311 If experiencing respiratory symptoms: Call a poison center/doctor.

P363 Wash contaminated clothing before reuse.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Date de révision

- · Department issuing SDS: Environment protection department.
- · Contact: Mr. Collins
- · Date of preparation / last revision 10/29/2021 / -
- · Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation - Category 2

 $\label{lem:eq:energy} \textit{Eye Irrit. 2A: Serious eye damage/eye irritation} - \textit{Category 2A}$

Resp. Sens. 1: Respiratory sensitisation – Category 1

Skin Sens. 1: Skin sensitisation – Category 1

Carc. 2: Carcinogenicity - Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

US