




# AUTOWASH



**INK DEGRADANT / SCREEN WASH**

**DILUTABLE WITH WATER**

AUTOWASH is formulated to be diluted with water to break down Plastisol and Water-Based inks. AUTOWASH is ideal for automatic screen washing and reclaiming machines. AUTOWASH effectively removes Plastisol and Water-Based ink stains.

## Advantages

- Ideal For Use in Automatic Reclaiming Equipment
- Easy to Use
- Economical - Can Be Diluted 1:1 or 1:2 With Water
- Reduces Labor
- Low Odor
- Immediately Breaks Down Ink
- High Flash Point
- Non-Hazardous
- High Solvency
- High Load Capacity to Reduce Usage
- Safe On All Types of Mesh
- Does Not Contain Alkylphenol Ethoxylates (APEO) / Nonylphenol Ethoxylates (NPEO)
- Does Not Contain HAPS (Hazardous Air Pollutants)

### Quick Tip

Dilute  
1:1 or 1:2  
with Water



## Application - Reclaim Machines


Dilute AUTOWASH 1:1 or 1:2 with water for use in your automated reclaim system.

## Application - Manual


INK WASHOUT AT THE SINK:

Card excessive ink from the screen. Apply AUTOWASH to ink side of screen. Use a non-abrasive scrub brush or pad to agitate ink on both sides of screen. Finally, rinse away all residue away.

1. Apply



2. Scrub



3. Rinse



Sizes:  Quart  1 Gallon  4x1 Gallon  5 Gallon  55 Gallon