

GR-80 (APEO / NPEO FREE) Textile & Graphic Multi-Purpose Screen Wash

### **General Description**

GR-80 is a water soluble ink degradent. It is highly effective on enamel, epoxy, multi-purpose (solvent based), plastisol, poster, UV, water based, and vinyl inks. GR-80 will protect the fabric from deep stains or ghosting from the image print. This makes it much easier when complete reclamation of the screen is necessary. GR-80 can be used in a wide variety of innovative cleaning processes ranging from re-circulation machines, dip tanks, immersion cleaning processes, and automatic reclaiming machines. It can also be applied manually with a scrub pad, spray bottle, or pneumatic pump systems.


GR-80 is also an excellent plastisol ink haze (ghost) remover. It is non-hazardous (non-corrosive) and aggressively removes image stains from the mesh.

### **Advantages**

- · Low Odor
- High Solvency
- High Load Capacity To Reduce Usage
- · Non-Hazardous / Non-Flammable
- · Mesh Safe
- Multiple Applications

### **Applications**

Always card excessive ink from screen. Use one of the following applications.



# At The Sink:

Card excessive ink from the screen. Apply GR-80 to ink side of screen. Use a nonabrasive scrub brush or pad to agitate ink on both sides of screen. Finally, rinse all residue away using high pressure water.

#### Haze Remover:

After ink and emulsion have been removed. spray GR-80 on both sides of the screen. Scrub screen both sides with a nonabrasive brush or pad. Allow product to sit for a few minutes (depending on severity of stain). High pressure rinse screen working from bottom and moving upwards.

> 4 x 4 Stainless Steel **Recirculating Booth**

## Recirculating Wash:

Card excessive ink from the screen. This product can be continuously recirculated until product becomes too heavily soiled with solids. Used product may be filtered and reused.

Sizes Available:

Quart Gallon 4 x 1 Gallon

5 Gallon Pail

55 Gallon Drum

Quick Tip:

Always pressure wash screen from the bottom and work upwards.

This will prevent ink from locking back onto the mesh when coming in contact with the rinse water.

