# (C) Chemical Consultants INCORPORATED

### **LS-500**

#### **Textile Screen Wash / Stain Remover**

#### **General Description**

LS-500 is a water soluble ink degradent. It is highly effective on plastisol, poster, UV, and water-based inks. LS-500 will protect the fabric from deep stains or ghosting from the image print. This makes it much easier when complete reclamation of the screen is necessary.

LS-500 can be used in a wide variety of innovative cleaning processes ranging from re-circulation machines, dip tanks, immersion cleaning processes, and automatic reclaiming machines. It can also be applied manually with a scrub pad, spray bottle, or pneumatic pump systems.

LS-500 is also an excellent plastisol ink haze (ghost) remover and aggressively removes image stains from the mesh.


#### **Advantages**

- Water-Based
- Low Odor
- High Solvency
- High Load Capacity To Reduce Usage
- Mesh Safe
- Multiple Applications

#### **Application**

Always card excessive ink from screen. Use one of the following

4 x 1 Gallon



#### Ink Wash-Out At The Sink

Sizes Available:

Quart

Card excessive ink from the screen. Apply LS-500 to ink side of screen. Use a non-abrasive scrub brush or pad to agitate ink on both sides of screen. Finally, rinse all residue away using high pressure water.

Gallon

#### Haze Remover:

After ink and emulsion have been removed, spray LS-500 on both sides of the screen. Scrub both sides of the screen with a non-abrasive brush or pad. Allow the product to sit for a few minutes (depending on severity of stain). High pressure rinse screen working from bottom and moving upwards.

## 4 x 4 Stainless Steel Recirculating Booth

55 Gallon Drum



#### Quick Tip:

Always pressure wash screen from the bottom and work upwards.

This will prevent ink from locking back onto the mesh when coming in contact with the rinse water.

1850 Wild Turkey Circle Corona, CA 92878 Phone (951) 735-5511 www.ccidom.com

5 Gallon Pail

**Recirculating Wash:** Card excessive ink from the screen. This product can be continuously recirculated until product becomes too heavily soiled with solids. Used product may be filtered and reused.