



# Chemical Consultants INCORPORATED

## MICROWASH II

2-n-1 Ink & Emulsion Stripper Concentrate

### General Description

MicroWash II is a water soluble, 2-n-1, ink degradant and emulsion remover. It is formulated to break-down UV and Plastisol Inks. MicroWash II will also remove all photo-polymer, diazo, and capillary film emulsions.

### Advantages

- Easy To Use
- Economical
- Water-Based
- Reduces Labor
- Low Odor
- NON-VOC (Volatile Organic Compounds)
- Immediately Breaks Down The Ink and The Emulsion
- High Flash Point / Non-Flammable
- Non-Hazardous
- High Solvency
- High Load Capacity To Reduce Usage
- Safe On All Types Of Mesh
- Biodegradable / Drain Safe
- Ideal For Use In Automatic Reclaiming Equipment
- Ideal For Dip Tank Applications
- Multiple Applications

#### Quick Tip:

Use a dilution that has plenty strength to break down the ink and emulsion.

Inks and emulsions that are not properly broken down, will leave excessive residue on the mesh.

### SCAQMD Bulletin:

MicroWash II is a NON-VOC stripper which meets the requirements of Southern California AQMD to be compliant of 100 grams VOC per liter or less.

### Applications

Dilute up to 1 to 5 with water.


MicroWash II can be applied by a sponge, pad, spray bottle, dip tank, or pneumatic pump systems.



**Step 1.** After removal of ink, and tape, apply MicroWash II to a wet screen(both sides).



**Step 2.** Scrub screen with non-abrasive pad or brush.



**Step 3.** High pressure rinse - starting at bottom.

### Dip Tank Application

Add MicroWash II to Dip Tank and fill with appropriate amount of water. UP TO 10 PARTS WATER.

Place screens in dip tank and let dwell for a few minutes. Only let screens soak until emulsion is soft enough to be rinsed off. Emulsion should not come off in dip tank.



**DT-3**

Polypropylene Dip Tank

### Sizes Available:

Quart  
5 Gallon Pail

Gallon  
30 Gallon Drum

4 x 1 Gallon  
55 gallon drum