



GENERAL DESCRIPTION

ProChem® 450L is a water soluble ink degradent. It is highly effective on plastisol, multi-purpose (solvent based), poster, UV and vinyl inks. ProChem® 450L will protect the fabric from deep stains or ghosting from the image print. This makes it much easier when complete reclamation of the screen is necessary.

ProChem® 450L can be used in a wide variety of innovative cleaning processes ranging from re-circulation machines, dip tanks, immersion cleaning processes, and automatic reclaiming machines. It can also be applied manually with a scrub pad, spray bottle, or pneumatic pump systems.

ADVANTAGES

- Low Odor
- High Solvency
- High load capacity to reduce usage
- High flash point / Non-flammable
- Non-Hazardous
- Mesh safe
- Will not attack cyanoacrylate (instant) adhesives
- Multiple applications

APPLICATIONS

Always card excessive ink from screen. Use one of the following applications.



4 x 4 Stainless Steel Recirculating Booth

[Click here for more details.](#)

RECIRCULATING WASH:

Card excessive ink from the screen. ProChem® 450L can be continuously recirculated until product becomes too heavily soiled with solids. Used product may be filtered and reused.

Available in:

1 gallon


5 gallon

55 gallon

Quick Tip:

Always pressure wash screen from the bottom and work upwards.

This will prevent ink from locking back onto the mesh when coming in contact with the rinse water.



INK WASH-OUT AT THE SINK:

Card excessive ink from the screen. Apply ProChem® 450L to ink side of screen. Use a non-abrasive scrub brush or pad to agitate ink on both sides of screen. Finally, rinse away all residue away using high pressure water.

Prochem® 450L