



**GENERAL DESCRIPTION**

ProChem® 508 is designed for all inks, especially vinyl, water base, epoxy, plastisol, enamel and UV inks. This product will perform as a press wash when changing colors between jobs and/or as a screen opener for continuous printing. ProChem® 508 will protect the fabric from deep stains or ghosting from the image print. This makes it much easier when complete reclamation of the screen is necessary. ProChem® 508 immediately liquifies the ink and dries quickly, leaves no film or oily residue.

**ADVANTAGES**

- Fast Drying
- Emulsion safe
- High solvency
- Low Odor
- High load capacity to reduce usage
- Mesh Safe

**Quick Tip:**


To cut down on the number of rags it takes to clean a screen, use a non absorbent scrub pad to liquify the ink and a squeegee to pull all the ink to one end of the screen and wipe up with one or two rags.

**APPLICATION**


First card excessive ink from the screen.

ProChem® 508 can be applied manually with a rag, spray bottle, or pneumatic pump systems.

**PRESS WASH AND SCREEN OPENER**



Step 1 . Spray **ProChem® 508** on the squeegee side of screen.



Step 2 . Scrub ink with a non-absorbent pad until liquified.



Step 3 . Use rags or towels to wipe up ink residue. Re-apply to clean up ink residue in image area.

**Available in:**

1 gallon

5 gallon

55 gallon

**ProChem® 508**